



**PROFESSIONAL CAR CARE DETAILING
PRODUCTS AND ACCESSORIES**

1.888.712.6227

Flex



Flex Variable-Speed Polisher

Variable-speed polisher with a high torque. Powerful 1400 watt motor with highly-efficient ventilator for optimum cooling. Grip hood is ergonomically shaped with SoftGrip. The machine can be controlled with precision and is always comfortable yet secure to hold.

Technical Specifications:

- Max. polishing pad diameter: 200 mm
- Max. back-up pad diameter: 150 mm
- No load speed: 380-2100 rpm
- Power input: 1400 watt
- Power output: 880 watt
- Tool fixture: M 14
- Size (L x H): 405x117 mm
- Cable length: 4,0 m
- Weight: 2,3 kg
- VR electronic control: stepless speed selection, tachogenerator-controlled constant speed, overload protection, re-start protection and temperature monitoring

Flex Velcro Backing Pad

Flex velcro backing pad for XC3401VRG. 5.5 inches.



Flex Orbital Polisher

Positive-drive orbital polisher. 8 mm orbit for high efficiency. Permanent direct drive for an even polished surface. VR microprocessor control; with tachogenerator constant speed control soft start, continuous speed control trigger, restart protection after power failure, overload protection, temperature monitoring and speed selection.

Technical Specifications:

- Max. polishing pad diameter: 160 mm
- Velcro backing pad Ø: 140 mm
- No load speed: 160-480 rpm
- Orbit: 8 mm
- Orbit rate, no load: 3200-9600 opm
- Power input: 1010 watt
- Power output: 590 watt
- Cable length: 4,0 m
- Weight: 2,6 kg